



**MATERIAL SAFETY DATA SHEET**

**PRODUCT NAME: AIR, COMPRESSED**

**1. Chemical Product and Company Identification**

**BOC Gases,  
Division of,  
The BOC Group, Inc.  
575 Mountain Avenue  
Murray Hill, NJ 07974**

**BOC Gases  
Division of  
BOC Canada Limited  
5975 Falbourne Street, Unit 2  
Mississauga, Ontario L5R 3W6**

**TELEPHONE NUMBER: (908) 464-8100  
24-HOUR EMERGENCY TELEPHONE  
NUMBER: CHEMTREC (800) 424-9300**

**TELEPHONE NUMBER: (905) 501-1700  
24-HOUR EMERGENCY TELEPHONE  
NUMBER: (905) 501-0802  
EMERGENCY RESPONSE PLAN NO: 2-0101**

**PRODUCT NAME: AIR, COMPRESSED; COMPRESSED OXYGEN AND NITROGEN MIXTURE  
CHEMICAL NAME: Oxygen (18.8-23.5%) in Nitrogen  
COMMON NAMES/SYNONYMS: Air, Compressed  
TDG (Canada) CLASSIFICATION: 2.2  
WHMIS CLASSIFICATION: A**

**PREPARED BY: Loss Control (908)464-8100/(905)501-1700.  
PREPARATION DATE: 6/1/95  
REVIEW DATES: 6/1/99**

**2. Composition, Information on Ingredients**

**EXPOSURE LIMITS<sup>1</sup>:**

INGREDIENT	% VOLUME	PEL-OSHA <sup>2</sup>	TLV-ACGIH <sup>3</sup>	LD <sub>50</sub> or LC <sub>50</sub> Route/Species
Oxygen FORMULA: O <sub>2</sub> CAS: 7782-44-7 RTECS #: RS2060000	18.8-23.5	Not Available	Not Available	Not Available
Nitrogen FORMULA: N <sub>2</sub> CAS: 7727-37-9 RTECS #: QW9700000	76.5-81.2	None Established	Simple Asphyxiant	Not Available

<sup>1</sup> Refer to individual state of provincial regulations, as applicable, for limits which may be more stringent than those listed here.

<sup>2</sup> As stated in 29 CFR 1910, Subpart Z (revised July 1, 1993)

<sup>3</sup> As stated in the ACGIH 1998-1999 Threshold Limit Values for Chemical Substances and Physical Agents.

OSHA Regulatory Status: This material is classified as hazardous under OSHA regulations.

**3. Hazards Identification**

**EMERGENCY OVERVIEW**  
Colorless, odorless nonflammable compressed gas. This product contains sufficient oxygen to support combustion and respiration. Contents under pressure. Use and store below 125 °F.

**PRODUCT NAME: AIR, COMPRESSED**

**ROUTE OF ENTRY:**

Skin Contact No	Skin Absorption No	Eye Contact No	Inhalation No	Ingestion No
--------------------	-----------------------	-------------------	------------------	-----------------

**HEALTH EFFECTS:**

Exposure Limits No	Irritant No	Sensitization No
Teratogen No	Reproductive Hazard No	Mutagen No
Synergistic Effects None reported		

Carcinogenicity: -- NTP: No IARC: No OSHA: No

**EYE EFFECTS:**

None known.

**SKIN EFFECTS:**

None known.

**INGESTION EFFECTS:**

None known. Ingestion is unlikely as product is gas at room temperature.

**ACUTE INHALATION EFFECTS:**

None expected. This product contains sufficient oxygen to sustain life.

This product is not intended for use as breathing air.

**MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:** None known.

**NFPA HAZARD CODES**

Health: 0  
Flammability: 0  
Instability: 0

**HMIS HAZARD CODES**

Health: 0  
Flammability: 0  
Reactivity: 0

**RATINGS SYSTEM**

0 = No Hazard  
1 = Slight Hazard  
2 = Moderate Hazard  
3 = Serious Hazard  
4 = Severe Hazard

**4. First Aid Measures**

**EYES:**

None required.

**SKIN:**

None required.

**INGESTION:**

None required.

**INHALATION:**

None required.

**MSDS:** G-113

**Revised:** 6/1/99

PRODUCT NAME: AIR, COMPRESSED

## 5. Fire Fighting Measures

Conditions of Flammability: Nonflammable		
Flash point: None	Method: Not Applicable	Autoignition Temperature: None
LEL(%): None	UEL(%): None	
Hazardous combustion products: None		
Sensitivity to mechanical shock: None		
Sensitivity to static discharge: None		

### **FIRE AND EXPLOSION HAZARDS:**

Nonflammable, non-combustible. Cylinder may rupture violently from pressure when involved in a fire situation.

### **EXTINGUISHING MEDIA:**

None required. Use as appropriate for surrounding materials.

### **FIRE FIGHTING INSTRUCTIONS:**

Firefighters should wear a NIOSH/MSHA approved full-facepiece self-contained breathing apparatus (SCBA) operated in positive pressure mode and full turnout or bunker gear.

## 6. Accidental Release Measures

No hazard expected. Contact the appropriate emergency telephone number listed in Section 1 or call your closest BOC location if safety problems arise.

## 7. Handling and Storage

### **Electrical classification:**

Non-hazardous.

This gas mixture is non-corrosive and may be used with all common structural materials.

Use only in well-ventilated areas. Valve protection caps must remain in place unless container is secured with valve protection outlet piped to use point. Do not drag, slide or roll cylinders. Use a suitable hand truck for cylinder movement. Use a pressure reducing regulator when connecting cylinder to lower pressure (<3000 psig) piping or systems. Do not heat cylinder by any means to increase the discharge rate of product from the cylinder. Use a check valve or trap in the discharge line to prevent hazardous back flow into the cylinder.

Protect cylinders from physical damage. Store in cool, dry, well-ventilated area of non-combustible construction away from heavily trafficked areas and emergency exits. Do not allow the temperature where cylinders are stored to exceed 125 °F (52 °C). Cylinders should be stored upright and firmly secured to prevent falling or being knocked over. Use a "first in-first out" inventory system to prevent full cylinders being stored for excessive periods of time.

For additional recommendations, consult Compressed Gas Association Pamphlets P-1.

Never carry a compressed gas cylinder or a container of a gas in cryogenic liquid form in an enclosed space such as a car trunk, van or station wagon. A leak can result in a fire, explosion, asphyxiation or a toxic exposure.

## 8. Exposure Controls, Personal Protection

### ENGINEERING CONTROLS:

General ventilation.

### EYE/FACE PROTECTION:

Safety goggles or glasses as appropriate for the job.

### SKIN PROTECTION:

Protective gloves of material appropriate for the job.

### RESPIRATORY PROTECTION:

None normally required. Use as appropriate for the job.

### OTHER/GENERAL PROTECTION:

Safety shoes.

## 9. Physical and Chemical Properties

PARAMETER	VALUE	UNITS
Physical state (gas, liquid, solid)	: Gas	
Vapor pressure	: Above critical temp.	
Vapor density at STP (Air = 1)	: 1.0	
Evaporation point	: Not Available	
Boiling point	: -317.8	°F
	: -194	°C
Freezing point	: Not Available	
	: Not Available	
pH	: Not Applicable	
Specific gravity	: Not Available	
Oil/water partition coefficient	: Not Available	
Solubility (H <sub>2</sub> O)	: Slightly soluble	
Odor threshold	: Not Applicable	
Odor and appearance	: Colorless, odorless gas	

## 10. Stability and Reactivity

### STABILITY:

Stable

### INCOMPATIBLE MATERIALS:

None

### HAZARDOUS POLYMERIZATION:

Does not occur

## 11. Toxicological Information

Product is non-toxic.

**MSDS:** G-113

**Revised:** 6/1/99

PRODUCT NAME: AIR, COMPRESSED
-------------------------------

## 12. Ecological Information

No data given.

## 13. Disposal Considerations

Do not attempt to dispose of residual waste or unused quantities. Return in the shipping container PROPERLY LABELED, WITH ANY VALVE OUTLET PLUGS OR CAPS SECURED AND VALVE PROTECTION CAP IN PLACE to BOC Gases or authorized distributor for proper disposal.

## 14. Transport Information

PARAMETER	United States DOT	Canada TDG
PROPER SHIPPING NAME:	Air, Compressed	Air, Compressed
HAZARD CLASS:	2.2	2.2
IDENTIFICATION NUMBER:	UN 1002	UN 1002
SHIPPING LABEL:	NONFLAMMABLE GAS	NONFLAMMABLE GAS

## 15. Regulatory Information

### SARA TITLE III NOTIFICATIONS AND INFORMATION

#### SARA TITLE III – SECTION 313 SUPPLIER NOTIFICATION:

This product does not contain toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act (EPCRA) of 1986 and 40 CFR 372.

#### SARA TITLE III - HAZARD CLASSES:

Sudden Release of Pressure Hazard

## 16. Other Information

ACGIH	American Conference of Governmental Industrial Hygienists
DOT	Department of Transportation
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
OSHA	Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
SARA	Superfund Amendments and Reauthorization Act
STEL	Short Term Exposure Limit
TDG	Transportation of Dangerous Goods
TLV	Threshold Limit Value
WHMIS	Workplace Hazardous Materials Information System

Compressed gas cylinders shall not be refilled without the express written permission of the owner. Shipment of a compressed gas cylinder which has not been filled by the owner or with his/her (written) consent is a violation of transportation regulations.

### DISCLAIMER OF EXPRESSED AND IMPLIED WARRANTIES:

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purpose(s).